

Shaking Water Bath


BW101/201/400

Shaking width 10~40 mm
(Non-stage transmission)

Shaking speed 20~160 times / min

- Adjustable shaking width from 10 to 40 mm.
- Digital display of shaking frequency.
- Double spring shaking rack for stability.
- Drain pump is attached to BW201 and BW400.
- Fitted with service receptacle for Immersion constant temperature device BF type

Control Panel



12L
BW101

20L
BW201

30L
BW400


Note: Immersion constant temperature device BF201/401/501 are sold separately.
Above picture is an example of BF and BW combination use.

Specifications

Product code	221503	221504	221505
Model	BW101	BW201	BW400
Shaking type	Reciprocate shaking		
Shaking width	10 to 40 mm adjustable		
Shaking speed	20 to 160 times / min. (Non-stage transmission)		
Temperature control range	Room temperature +5 to 80°C (using Immersion constant temperature device BF type)		
Water bath material	Stainless steel		
Shaking speed control system	Feedback phase control		
Shaking speed display system	Digital display		
Additional function	Service receptacle AC100V, 12A for Thermomate BF201/401/501		
Usable fluid	Water only		
Drain type	Natural drain	Drain pump	
Safety device	Electric leakage breaker, Motor overheat prevention (Automatic recovery type thermal protector)		
Water bath internal dimension	W230×D390×H150mm	W300×D500×H150mm	W380×D535×H150mm
External dimensions*1	W295×D445×H285mm	W370×D560×H285mm	W445×D585×H295mm
Water bath capacity	Approx. 12L	Approx. 20L	Approx. 30L
Weight	Approx. 28kg	Approx. 35kg	Approx. 42kg
Power (50/60Hz)	AC220V 6A (using Immersion constant temperature device BF type) Single phase with step-down transformer		
Accessory	Shaking Rack		

*1 Do not include protrusions.

Service Receptacle



Shaking Rack



Number of containers stored

	BW101	BW201	BW400
Test tube (dia. 15mm)	60	126	190
Erlenmeyer flask (50mL)	10	21	30

